

Underscore® Rectangle

6' BubbleMassage™ Bath **K-1174-G**



Features

- 122 airjets release thousands of bubbles that surround, support, and massage the body.
- Variable-speed blower lets you adjust massage intensity to 18 levels.
- Zones of Control feature allows you to target massage to back, midsection, or feet.
- Lighted keypad.
- Generous 6-foot length provides spacious bathing for up to two people.
- Molded lumbar support offers extra comfort while bathing.
- Slotted overflow allows for deep soaking.
- Immediate and manual purge cycles remove residual water from air channels after use.
- Center drain.
- Under-mountable

Material

Acrylic

Hydrotherapy

BubbleMassage

Installation

Drop-in or under-mount.

Additional Hydrotherapy Options

- Soaking Bath 1137-0
- Soaking Bath + Bask heated surface 1137-W1
- BubbleMassage air bath 1174-G
- BubbleMassage air bath + chromatherapy 1174-GCR
- VibrAcoustic + BubbleMassage air bath 1174-GVB
- VibrAcoustic + BubbleMassage air bath + Bask heated surface + chromatherapy - 1174-GVBCW
- Whirlpool + heater 1174-H2
- VibrAcoustic 1174-VB
- VibrAcoustic + chromatherapy 1174-VBC
- VibrAcoustic + chromatherapy + Bask heated surface -1174-VBCW
- VibrAcoustic + Bask heated surface 1174-VBW
- Whirlpool + BubbleMassage air bath 1174-XH2G

Required Products/Accessories

K-7271 Brass Slotted Overflow Bath Drain

or

K-7272 PVC Slotted Overflow Bath Drain

Recommended Products/Accessories

K-1491 Bath/Whirlpool Pillow

Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 CSA C22.2 No. 218.2 Greenguard UL 2818 - Gold

KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty KOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	33	Mexican Sand™
	K4	Cashmere





Underscore® Rectangle

6' BubbleMassage™ Bath **K-1174-G**



Required Electrical Service

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Blower: 240 V, 15 A, 50/60 Hz

Technical Information

All product dimensions are nominal.

Installation: Drop-in, Under-mount

Drain location: Center

Basin area, bottom: 45-3/4" x 32" (1162 mm x 813 mm)
Basin area, top: 66" x 36" (1676 mm x 914 mm)

Weight: 110 lbs (49.9 kg)

 $Minimum \ floor \ load: \qquad 42 \ lbs/ft^2 \ (205.1 \ kg/m^2)$

Water depth: 19" (483 mm)
Water capacity: 139 gal (526.2 L)

Cutout: Drop-in, 70-1/2" x 40-1/2" (1791 mm x

1029 mm)

Electrical component Blower: 240 V, 5 A, 50/60 Hz

rating:

Blower speed: Variable
Minimum flat for door: 2-1/2" (64 mm)


Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Kit is required for under-mount installations (sold separately).

If relocating the blower motor, do not relocate or alter the PVC tee or coiled flexible tubing connected to the blower. Follow the blower relocation instructions exactly. Provide access for servicing the blower.



Kohler Co. reserves the right to make revisions without notice to product specifications. For the most current Specification Sheet, go to www.kohler.com. 5-25-2019 05:27 - US/CA/MX

