DESCRIPTION

Turnbuckles tighten and secure the cables and provide the necessary tension for a clean look. For long or turning runs (runs over 20'). Mount to wall or ceiling. When ceiling mounted, cables drop 2.5" from ceiling. Pair. 2" Minimum Cable Separation. If mounting to metal, order isolating connector (sold separately).

Kable Lite Universal Turnbuckles

INSTALLATION

All turnbuckles include mounting hardware for drywall. Special hardware is available for brick, cement, or plaster surfaces (sold separately). For all runs of over twenty feet, turnbuckles should be reinforced with wood blocking behind the wall.

WEIGHT

 $0.85lb / 0.39kg \pm$



kable lite universal turnbuckles

ORDERING INFORMATION

700PARTT LENGTH (A)

FINISH

2.5"

C CHROME S SATIN NICKEL

700PARTT

FIXTURE TYPE:



7400 Linder Avenue Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

Tech Lighting, L.L.C.

JOB NAME: NOTES:

1.8"

140 mm

2.5"

1.8"



©2019 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.