

Lineacurve 36 dual wall/ceiling 2-wire dimming

SPECIFICATIONS

RDLC3B93006AN



Design By

NA Design

Collection

Design



Specifications

Delivered lumens	2560lm
Light output ratio	44lm/W
Power consumption	58.8W
Led type	2X25W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire**
Input Voltage	120-277V
Driver	HATCH - 2 x XTC34-1050P-UNV-I

**Reverse or forward phase (120v only)

Colors & Finishes

Anthracite grey


Materials

- Body in extruded aluminum
- End caps in aluminum

Features & Accessories

- Extrusion covers junction box dimension

Dimensions




Packaging

1 Box

1 x 40-5/16" x 8-1/16" x 5-1/16" / 10.43 lbs - 102.24 cm x 20.32 cm x 12.7 cm / 4.73 kg

Light distribution

Direct/Indirect



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Luminaire weight

8.62 lbs / 3.91 kg

Warranty

5 year limited warranty,
Upon registration. Click [here](#)
to register your purchase.