


The Next Necessity



Dimensions



Instant Hot Water Dispensers



H-Classic-SS

Easy-grip handle to dispense instant near-boiling 200°F water effortlessly

Submittal Sheet

- Hot Only Dispenses near-boiling 200°F water
- Includes 2/3-gallon hot water tank
- Easy to adjust temperature control
- Tool-free tank connections and dry start
 protection to ease installation
- Provides 60 cups/hr of near-boiling water
- We Come To You® 3-Year In-Home
- Limited Warranty*
- 115 volts, 750 watts, 6.5 amps
- · Available in chrome
- · Unit not for commercial/industrial use

Specifications

Capacity	2/3-gallon hot water tank dispenses 60 cups of 200°F water per hour
Electrical	115 volts A.C., 750 watts, 6.5 amp heating element with grounded three (3) prong plug
Thermostat	Snap-action, adjustable from 160°F to 210°F (factory pre-set at 200°F)
Insulation	Meets U.L. 94HF-1 flammabiltiy specification
Valve	Instant, self-closing
Recommended Supply Pressure	30-125 psi
Shipping Weight	Approximately 7.4 lbs.
Required Hole Diameter	1-1/4"* - 1-1/2" standard sink hole



* For counters up to 3/4" thick

Sample Specification

Instant hot water dispenser(s) shall be InSinkErator Model H-Classic-SS with 2/3-gallon hot water tank, adjustable temperature from 160°F to 210°F and instant, self-closing hot valve.

Warranty:

3-year parts and in-home service.

* The complete InSinkErator warranty is included in the Care & Use booklet packed with each unit.

US Patent Pending (tank enclosure)

Job Specifications













Complies with California Lead Plumbing Law



Commercial & Residential Solutions

The Emerson logo is a trademark and a service mark of Emerson Electric Co.

InSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models.

© 2016 InSinkErator, InSinkErator® is a business unit of Emerson Electric Co. All Rights Reserved.



1-800-558-5700