T417300W08



Design By -

Ernesto Gismondi

Collection ==

Outdoor



Colors & Finishes =



Materials =

- Lamp support in extruded aluminum
- Base in painted steel
- Lighting unit in die-cast aluminum
- Reflectors in metallic polycarbonate
- UV resistant diffuser in shock resistant polycarbonate


Specifications —

Delivered lumens	434lm
Light output ratio	29.32lm/W
Power consumption	14.8W
Led type	14W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120V
Driver	MEAN WELL - 1 x APC-16-350
BUG Rating	B0-U3-G1

Features & Accessories =

- Base contains holes for wall installation
- Provided with cable and IP67 connector
- Electronic driver integrated
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

Dimensions =




Packaging =

1 Box

1 x 10-3/4" x 10-3/4" x 7-15/16" / 5.29 lbs - 27 cm x 27 cm x 20 cm / 2.4 kg

Light distribution —

Diffused



Luminaire weight —

3.97 lbs / 1.8 kg

Warranty
5 year limited warranty

Red = Max Cd. Through Vertical plane
Blue = Max Cd. Through Horizontal plane