

# Round flush mount

Our LED flush mounts incorporate edge-lit technology, eliminating hot spots and glare. With 4 sizes to choose from, every application is covered.



WET



COLOR TEMPERATURE



**JA8**  
CERTIFIED\*



\*Models CFLEDR06, CFLEDR10, and CFLEDR14 only

Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>CFLEDR06-CC</b>	6"	11 W	700 lm	750 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
<b>CFLEDR10-CC</b>	10"	17 W	1000 lm	1200 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
<b>CFLEDR14-CC</b>	14"	26 W	1600 lm	2100 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
<b>CFLEDR18-CC</b>	18"	30 W	2100 lm	2500 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V

### Specifications

Integrated dimmable driver  
 Over 50,000 hours of service life  
 Switch-selectable CCT: 2700 K/  
 3000 K/3500 K/4000 K/5000 K in canopy  
 Smooth 360° wide spread  
 Minimal heat emission  
 Frosted lens  
 Edge-lit technology  
 Cast aluminum construction  
 Suitable for wet locations  
 Refer to website for dimmer compatibility  
 Ideal operating temperature:  
 -20° to 40° C  
 5-year warranty

### Finish

- **BB** Brushed Brass  
(CFLEDR06, CFLEDR10, CFLEDR14 only)
- **BK** Black
- **SN** Satin Nickel
- **WH** White

### Order example


**CFLEDR06-CC-SN**  
 CFLEDR06-CC 6" round ceiling flush mount  
 in a satin nickel finish

### Note


Other Color °T and Finishes available, but  
 may require MOQ's and longer lead times.  
 Please contact your DALs representative  
 for more information.




**CFLEDR06-CC**



**CFLEDR10-CC**



**CFLEDR14-CC**



**CFLEDR18-CC**

