# Tetragono 45 floor

# SPECIFICATIONS

Ĩ	Design By Ernesto Gismondi	Specifications	
		Delivered lumens	504lm
		Light output ratio	34.52lm/W
	Collection	Power consumption	14.6W
	Outdoor	Led type	14W Array*
		CCT (Correlated Color Temperature)	3000K
		CRI (Color Rendering Index)	>80
		Life expectancy	50000Hrs
	(III) c(H) us (IP65)	Control type	On/Off
Colors & Finishes		Input Voltage	120V
Anthracite grey		Driver	MEAN WELL - 1 x APC-16-350
		BUG Rating	B0-U2-G0
Materials			
<ul><li>Lamp support in painted extruded aluminum</li><li>Base in painted steel</li></ul>		Features & Accessories	
		<ul> <li>Base contains holes for floor installation by means of log bolts and dowels</li> </ul>	

- Lighting unit in die-cast aluminum
- Reflectors in metallic polycarbonate
- UV resistant diffuser in shock resistant polycarbonate

• Provided with cable and IP67 connector

• Electronic driver integrated

Standard non dimmable


• For dimming options, please consult with your Artemide Sales Representative

#### Dimensions —

### Packaging =


1 Box

1 x 9-1/8" x 9-1/8" x 27-5/8" / 9.92 lbs - 23 cm x 23 cm x 70 cm / 4.5 kg




## Light distribution =

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane Warranty 5 year limited warranty



We reserve the right to change specifications of our products. For the latest product information please visit www.artemide.net

