

Tetragono 90 floor

T417200W08

SPECIFICATIONS



Design By

Ernesto Gismondi

Collection

Outdoor



Specifications

Delivered lumens	504lm
Light output ratio	34.52lm/W
Power consumption	14.6W
Led type	12W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120V
Driver	MEAN WELL - 1 x APC-16-350
BUG Rating	B0-U2-G0

Colors & Finishes

■ Anthracite grey


Materials

- Lamp support in painted extruded aluminum
- Base in painted steel
- Lighting unit in die-cast aluminum
- Reflectors in metallic polycarbonate
- UV resistant diffuser in shock resistant polycarbonate

Features & Accessories

- Base contains holes for floor installation by means of log bolts and dowels
- Provided with cable and IP67 connector
- Electronic driver integrated
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

Dimensions




Packaging

1 Box

1 x 11-1/8" x 7-3/8" x 45-3/4" / 15.54 lbs - 28 cm x 18.5 cm x 116 cm / 7.05 kg

Light distribution

Direct



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Luminaire weight

11.9 lbs / 5.4 kg

Warranty

5 year limited warranty