Obice wall 34° T430534W18

SPECIFICATIONS



Design By

Alessandro Pedretti

Collection —



Colors & Finishes

Black

Materials =

- Body in injection molded aluminum
- Terminal base and adjustable joint in injection molded aluminum
- Diffuser in 1/64" (4mm)-thick tempered glass with black opal serigraphy

Specifications	
Delivered lumens	605lm
Light output ratio	60.5lm/W
Power consumption	10W
Led type	8W Array*
CCT (Correlated Color Temperature)	3000К
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120V
Driver	MEAN WELL - 1 x LPC-20-700
BUG Rating	B1-U0-G0

Features & Accessories -

• Tilting angle +35°/-125°


• Rotation on horizontal axis 359°

- Wiring to be carried out by means of a plug located in the terminal base
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

Packaging —


1 Box

1 x 12-11/16" x 12-11/16" x 8-9/16" / 5.25 lbs - 32 cm x 32 cm x 21.5 cm / 2.38 kg



Light distribution —

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane Luminaire weight

Warranty 5 year limited warranty

last updated: 2020-02-24

