

Nuda 50 bilateral floor white

SPECIFICATIONS

T083708



Design By

Ernesto Gismondi

Collection

Outdoor



Specifications

| | |
|------------------------------------|-------------------------------|
| Delivered lumens | 147lm |
| Light output ratio | 18.38lm/W |
| Power consumption | 8W |
| Led type | 6X6.8W Array* |
| CCT (Correlated Color Temperature) | 3000K |
| CRI (Color Rendering Index) | >80 |
| Life expectancy | 50000Hrs |
| Control type | On/Off |
| Input Voltage | 120V |
| Driver | MAGTECH - 1 x LA1012-36-C0350 |
| BUG Rating | B0-U2-G0 |

Colors & Finishes

White RAL9002


Materials

- Body in aluminum
- UV resistant diffuser in shock resistant polycarbonate

Features & Accessories

- Provided with IP65 cables and connector for the main connections
- Mounting plate contains holes for ground fixing by means of included lock bolts and dowels
- Electronic driver integrated in body
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

Dimensions



Packaging

1 Box


1 x 11-1/2" x 11-1/2" x 25-5/16" / 11.6 lbs - 29 cm x 29 cm x 64 cm / 5.26 kg

Light distribution

Direct

Luminaire weight

7.94 lbs / 3.6 kg



Warranty

5 year limited warranty

Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane