


Submitted Model No.: \_ Specific Features:



- ▲ Designate proper finish suffix
- Your Delta Faucet handshower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Delta can do

# HAND SHOWER

■ Five Spray Setting Hand Shower

## **FEATURES:**

■ Touch-Clean® Nozzles

### STANDARD SPECIFICATIONS:

- Maximum 1.75 qpm @ 80 psi, 6.6 L/min @ 550 kPa
- Hand held shower with five spray patterns
- 60"-82" (1524 mm 2083 mm) stretchable metal hose
- Adjustable shower arm mount for hands-free showering

#### WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



#### **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1 ◆
- ASME A112.18.3
- EPA WaterSense®

**Delta Faucet Company** 55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON NSP 4L1 © 2018 Delta Faucet Company