

WAC LIGHTING

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Princess

Beauty Spot 3000K

| Model & Wattage | Lumens | Color Temp & CRI | Finish |
|----------------------|--------|------------------|--------------------|
| DR-362 Xenon : 20W | 200 | 3000K | CL/CH Clear/Chrome |
| DR-362LED LED : 4.5W | 150 | 3000K 90 | |

Example: **DR-362-CL/CH**

DESCRIPTION

Polished and cut by hand from optic crystals to create sparkling patterns of light. An impressive custom crystal display arranged in a pattern or in a random array on walls or ceilings. Smooth and continuous ELV dimming.

FEATURES

- Sold as complete unit - housing and trim
- Use 12V/24V Class 2 remote electronic transformer (order separately)
- Easily mounted on suspended or finished ceilings
- Can be used individually as accent pieces or grouped together
- LED and Xenon versions are dimmable with ELV dimmers
- Rated Life: LED 50,000 Hrs, Xenon 10,000 Hrs
- 5 year warranty

SPECIFICATIONS

| | |
|------------------------|--|
| Construction: | Chrome plated faceplate with steel black powder coated wiring compartment |
| Power: | LED : 4.5W, Xenon : 20W |
| Input: | 50/60Hz, LED : 24 VAC, Xenon : 12 VAC |
| Dimming: | ELV: 100-10% |
| Light Source: | Integrated LED, Xenon Bi-Pin |
| Lens: | Optical Crystal |
| Mounting: | No screws, nails or hardware required. Flat "wing" springs expand against the cut out hole to hold fixture against the surface; Integral wiring compartment with standard size knock out hole on top., Can be mounted on ceiling or wall in all orientations |
| Cut Out: | 2 3/8" |
| Finish: | Electroplated Clear/Chrome |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | UL, cUL, Damp Location Listed |




FINISHES



Clear/
Chrome

LINE DRAWING



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Enclosed Electronic Transformer 120V/12V Class 2 Power Supply

Model & Product

| Model | Product Description | L x W x H |
|--------------|--|----------------------------|
| EN-1260-RB2 | Enclosed Electronic Class 2 Transformer 120V Input 12V Output 60 Watt | 6.625IN x 1.625IN x 1.25IN |
| EN-12120-RB2 | Enclosed Electronic Class 2 Transformer 120V Input 12V Output 120 Watt | 6IN x 3.25IN x 2.625IN |
| EN-12180-RB2 | Enclosed Electronic Class 2 Transformer 120V Input 12V Output 180 Watt | 6.75IN x 3.625IN x 2.625IN |
| EN-12300-RB2 | Enclosed Electronic Class 2 Transformer 120V Input 12V Output 300 Watt | 8.25IN x 4.625IN x 2.625IN |

DESCRIPTION

Example: EN-1260-RB2
An enclosed electronic transformer is the perfect solution for wiring multiple low voltage fixtures. WAC transformers are intrinsically safer transformers because they are compartmentalized to allow no greater than 5 amps of current to be drawn on each compartment. Secondary wiring for transformers do not require conduit sheathed cable or clamp wiring techniques. This transformer has a low minimum load requirement of 1W to allow the use of LED products. May be dimmed using an electronic low voltage dimmer.

FEATURES

- 1W minimum load
- Use for all initial installations to ensure safe and primary side connections in a wiring compartment
- Dimming with Electronic Low Voltage dimmers
- All connections must be made in an enclosure for proper installations
- Secondary wiring for Class 2 transformers does not require conduit sheathed cable or clamp wiring techniques
- Non-metallic sheathed cable may be used for secondary wiring in walls and ceilings
- Drop down to a smaller gauge wire if space in fixture does not permit secure connection directly with the non-metallic sheathed cable
- Built-in auto reset, soft start, short and overload circuit
- 5 year warranty

SPECIFICATIONS

| | |
|-----------------|--------------------------------|
| Input: | 120 VAC, 50/60Hz |
| Finish: | Black |
| Operating Temp: | -40°F to 122°F (-40°C to 50°C) |
| Standards: | UL, cUL |



FINISHES



Black

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Class 2 Enclosed Electronic Transformer

120V/24V Power Supply

| Model & Max Output Power | Product | L x W x H |
|--------------------------|---|--------------------------|
| EN-24100-RB2-100 | Electronic Class 2 Transformer 120V Input 24V Output 60 Watt | 6.51N x 1.625IN x 1.25IN |
| EN-2460-RB2-60 | Electronic Class 2 Transformer 120V Input 24V Output 100 Watt | |

Example: **EN-2460-RB2**

DESCRIPTION

This class 2, UL & cUL listed enclosed electronic transformer is the perfect solution for wiring multiple low voltage fixtures. Class 2 transformers are intrinsically safer transformers because they are compartmentalized to allow no greater than 5 amps of current to be drawn on each compartment. Enclosure cover is easy to remove. Transformer has knockouts on three sides with clips for line voltage wiring. Secondary wiring for class 2 transformers do not require conduit sheathed cable or clamp wiring techniques. This transformer has a low minimum load requirement of 1W to allow the use of LED products. May be dimmed using an electronic low voltage dimmer.

FEATURES

- 1W minimum load
- Secondary wiring for Class 2 transformers does not require conduit sheathed cable or clamp wiring techniques
- Intrinsically safe, Class 2 transformers permit no greater than a 5 amp current be drawn
- Non-metallic sheathed cable may be used for secondary wiring in walls and ceilings
- Drop down to a smaller gauge wire if space in fixture does not permit secure connection directly with the non-metallic sheathed cable
- Dimming with Electronic Low Voltage dimmers
- 5 year warranty

SPECIFICATIONS

| | |
|-----------------|--------------------------------|
| Input: | 120 VAC, 50/60Hz |
| Finish: | Black |
| Operating Temp: | -40°F to 122°F (-40°C to 50°C) |
| Standards: | UL, cUL |



FINISHES



Black