





PRODUCT DESCRIPTION

With cutting-edge smart controls and a totally quiet DC motor, Morpheus is a sleek piece of luxury in a stylish two- or three-blade design. Like all our smart fans, Morpheus connects through Wi-Fi to our exclusive Modern Forms app, so it doesn't matter if you're five feet away or five hundred miles away- control is always in the palm of your hand. A powerful LED luminaire with artisan-crafted opal glass and thick aerodynamically soundless blades round out the design. Available in four amazing finishes.

SPECIFICATIONS

Construction: ABS

Blade: 12° Pitch, 60" sweep, ABS **Downrod:** 1" O.D. x 4.5"H included **Mounting Slope:** Up to 30°

Lead Wire: 80" Hanging Weight: 17 lbs Total Power: 50.5W

Standards: ETL/cETL Wet Location listed

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Optional RF remote control with wall cradle sold separately
- Compatible with Modern Forms app

LIGHT KIT PERFORMANCE

Light Source: LED Light Wattage: 19.5 Dimming: Integrated

Color Temperature: 3000K (2700K / 3500K options available)

Rated Life: 50,000 Hours

Standards: Title 24 JA8-2016 Compliant

ESTIMATED AIR PERFORMANCE

Airflow: 7490 cubic ft per minute on high

Power: 31 watts on high

Airflow Efficiency: 243 cubic ft per minute per watt **Revolutions Per Minute:** 142 RPMs on high

WIRELESS PERFORMANCE

RF Pairing Distance: Up to 30 ft from fan

Wi-Fi Range: Up to 150 ft*

ORDER NUMBER

OIGE LICE TO THE EAST						
Model	LED	Delivered		Housing	Blade	
	Lumens	Lumens				
FR-W1813-60L		1142	GW	Gloss White	Gloss White	
	1600		AS	Automotive Silver	Automotive Silver	
	1600		CFI	Carbon Fiber	Carbon Fiber	
			DW	Dark Walnut	Dark Walnut	

Example: FR-W1813-60L-BZ

For 2700K add "-27"; 3500K add "-35" before the finish: FR-W1813-60L-27-AS

*Results may vary based on application and surroundings.









modernforms.com Phone (866) 810.6615 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

MORPHEUS III 60" Ceiling Fan

FR-W1813-60L



OPTIONAL ACCESSORIES				
RF Wall Control	F-WC	w	/T White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.
RF Remote Control	F-RC	w	/T White	Sold separately. Control fan speed and light brightness, and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.
Wi-Fi Touch Panel Wall Control	F-TS	BH		Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
Downrod Couplers	XF-18 1 XF-24 2 XF-36 3 XF-48 4 XF-60 6	22in	Brushed Aluminum Z Bronze FI Carbon Fiber** W Dark Walnut B Gloss Black H Graphite W Gloss White	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field. Connects two downrods together.
Sloped Ceiling Kit	loped Ceiling Kit XF-SCK		Matte Black Matte White B Oil Rubbed Bronze S Stainless Steel T Titanium Silver	Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: RF Wall Control - **F-WC-WT**, RF Remote Control - **F-RC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15′	14′	13'	12′	11'	10′	9′
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

**Carbon Fiber downrods available in 12", 18", 24" and 36"

†Koa downrods available in 12", 18", 24" and 36"

modernforms.com Phone (866) 810.6615 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760