


Starck 3 Toilet close-coupled # 214109..92

< 14 5/8" Inch >



Toilet close-coupled	Dimension	Weight	Order number
(without tank), washdown model, suitable for SensoWash Starck, hardware included, cUPC listed			
Colors			
00 White 20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness)			
Variant			
<ul style="list-style-type: none"> 1.6/0.8 gpf, outlet for vario connector set, for horizontal and vertical outlet, length adjustable from 2 3/4" - 7 7/8", and vario 14 5/8" x 27 3/4" Inch connecting bend, vertical outlet from 6 1/4" - 7 7/8" 		75.6 lb	214109..92
Infobox			
For suitable SensoWash® shower-toilet seats, please see matrix on page xxx			

Starck 3 Toilet close-coupled # 214109..92

|< 14 5/8" Inch >|

Sanitary ceramics with the special WonderGliss surface finish will remain clean and attractive-looking for a long time to come.
When ordering WonderGliss please add a "1" as eleventh digit to the model number.

Vario connecting bend for vertical outlet			1.5 lb	899025
Vario connector set incl. offset	Ø 4 3/8" Inch		3.3 lb	001422
Suitable products				
Tank cUPC listed, for bottom left supply, 15 3/8" x 7 1/4" Inch	15 3/8" x 7 1/4" Inch			092010
Toilet seat and cover elongated, hinges stainless steel, removable, with slow close,				006339
SensoWash Starck shower-toilet seat for Starck 2, Starck 3 and Darling New* remote control included, power actuated lid and seat, rear-, front and oscillating wash, individual adjustment of water-, air- and seat surface temperature as well as nozzle position and jet strength, self-cleaning wand, 2 individually programmable user profiles, night light, Quick release: easy seat unit removal and attachment, on / off-button, 14 5/8" x 20 1/4" Inch	14 5/8" x 20 1/4" Inch			610000
Toilet seat and cover elongated, hinges stainless steel, without slow close,				006332

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.