



Naoto Fukasawa

Collection =

Design



Colors & Finishes =



Materials =

- Head and arms in painted aluminum
- Lower head diffuser in thermoplastic
- Internal tension springs and external tension control cables in aluminum
- Wall support in painted aluminum


Specifications —

| Delivered lumens | 392lm |
|------------------------------------|---------------------------------------|
| Light output ratio | 43.56lm/W |
| Power consumption | 9W |
| Led type | 8.5W Array* |
| CCT (Correlated Color Temperature) | 3000K |
| CRI (Color Rendering Index) | >80 |
| Life expectancy | 50000Hrs |
| Control type | DIMMABLE (On Head) / No Motion Sensor |
| Input Voltage | 120-240V |
| Driver | Plug-In |

Features & Accessories =


- Fully adjustable arms and head
- Tiltable and rotatable diffuser
- Interchangeable plug options accommodate most electrical outlets for global versatility

Dimensions =



Light distribution =

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Packaging =

2 Boxes

1 x 42" x 14" x 2-5/8" / 5.51 lbs - 106.5 cm x 35.5 cm x 6.5 cm / 2.5 kg

1 x 7-15/16" x 7-15/16" x 6-3/8" / .77 lbs - 20 cm x 20 cm x 16 cm / .35 kg

Luminaire weight ==

1.87 lbs / .85 kg

Warranty =

5 year limited warranty

