DEM1055



Naoto Fukasawa

Collection =

Design







Colors & Finishes =



Specifications =

Delivered lumens	392lm
Light output ratio	43.56lm/W
Power consumption	9W
Led type	8.5W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	DIMMABLE (On Head) / No Motion Sensor
Input Voltage	120-240V
Driver	Plug-In

Materials =

- Head and arms in painted aluminum
- Lower head diffuser in thermoplastic
- Internal tension springs and external tension control cables in aluminum
- In-set pivot made in die-cast aluminum with matching painted finish

Features & Accessories =

- Fully adjustable arms and head
- Tiltable and rotatable diffuser


Packaging = 2 Boxes

• Interchangeable plug options accommodate most electrical outlets for global versatility


1 x 42" x 14" x 2-5/8" / 5.51 lbs - 106.5 cm x 35.5 cm x 6.5 cm / 2.5 kg

1 x 5-3/16" x 5-3/16" x 3-5/8" / .44 lbs - 13 cm x 13 cm x 9 cm / .2 kg

Dimensions =




46.5 cm




Light distribution

Direct



Luminaire weight

1.54 lbs / .7 kg



Warranty =

Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane