

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Vornado Pendant 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
PD-87729 29"	3000K 90	87W	7766	5375	CH Chrome

Example: **PD-87729-CH**

DESCRIPTION

Harmony out of chaos, Vornado is a free flowing mobius strip of high-powered LED illumination. A simple, yet dynamic piece, Vornado is hand crafted to perfection. The flexible" composite diffuser maximizes brightness and eliminates LED hot spot. Vornado is suspended on four thin low profile cables without the need for an additional power cord, lending to a " simple and minimalistic design. Adjustable to different lengths through a push-pin locking mechanism at the canopy.

FEATURES

- Hand-crafted, asymmetric & seamless construction, variation expected
- Thin powered cables provide an ultra-clean look
- Can be mounted on a sloped ceiling
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120-277 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%, 0-10V: 100 - 5%
Rated Life:	50000 Hours
Standards:	ETL, cETL, Title 24: 2016 Damp Location Listed
Construction:	Aluminum body with flexible composite diffuser




FINISHES



Chrome

LINE DRAWING



PD-87729

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Vornado Pendant 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
PD-87741 41"	3000K 90	87.5W	7818	5861	CH Chrome

Example: **PD-87741-CH**

DESCRIPTION

Harmony out of chaos, Vornado is a free flowing mobius strip of high-powered LED illumination. A simple, yet dynamic piece, Vornado is hand crafted to perfection. The flexible" composite diffuser maximizes brightness and eliminates LED hot spot. Vornado is suspended on four thin low profile cables without the need for an additional power cord, lending to a " simple and minimalistic design. Adjustable to different lengths through a push-pin locking mechanism at the canopy.

FEATURES

- Hand-crafted, asymmetric & seamless construction, variation expected
- Thin powered cables provide an ultra-clean look
- Can be mounted on a sloped ceiling
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120-277 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%, 0-10V: 100 - 5%
Rated Life:	50000 Hours
Standards:	ETL, cETL, Title 24: 2016 Damp Location Listed
Construction:	Aluminum body with flexible composite diffuser




FINISHES



Chrome

LINE DRAWING



PD-87741