

SWING

Design by Lievore Altherr Molina.

VIBIA

Reference

0514.

Application

Wall Fixtures

Installation type

Surface mounted

Description

The SWING floor, table and wall sconce collection was updated to feature a new, clean look, as well as 2 new finishes. Each member of this family possesses a jointed arm allowing for a wide 180° range of motion for directional ambient illumination. Reference 0514 also includes a directional LED reading light. Collection available in three finishes: chrome, graphite grey and matte white.

Diffuser

PMMA diffuser

Materials

Wall support: Aluminum

Horizontal tube: Steel

Finishes



0514-01 Chrome (Metallic finish)




0514-18 Black (RAL 7016)



0514-93 White (RAL 9016)

Sketch



Electrical characteristics

1 x A-19 LED LAMP 120V 8W

AND

1 x LED 2.1W 700mA

Total 2.1 W



Light source: 3000K CRI >80

Fixture: 414 lm 24 lm/W

Driver included: CC - Constant Current 700 mA 120V 50Hz

Electronic dimming: NO DIMMING

Technical characteristics

- Switch located on the lampholder


Installation and assembly

Please see the installation manual

Light distribution

Reading

Lamp having a light beam whose main function is to supply sufficient light for reading.



Photometric data

Efficiency : 3%

Total flux : 781.22

Maximum value : 447.92

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=3.00m

Certificates

