CORSO - LED Pendant PD-33718, PD-33732, PD-33743, PD-33753

dwe	LED
	by WAC Lighting



Fixture Type: Catalog Number: Project:

PRODUCT DESCRIPTION

Cleverly hidden LED modules and a circular frosted diffuser floating inside a halo of spun aluminum.

FEATURES

- Acrylic diffuser to provide even illumination with no LED hotspots
- Thin powered aircraft cables provide an ultra-clean look
- Can be mounted on a sloped ceiling
- Universal voltage driver (120V 220V 277V) concealed within canopy.
- Color Temperature: 3000K
- CRI: 90
- Rated Life: 75,000 hours

SPECIFICATIONS

Construction: Aluminum with acrylic diffuser.

Input: 120V - 277V


Dimming: 100% - 10% ELV 100% - 5% 0-10V


Location:

Light Source: High output LED

Finish: White (WT), Black (BK), Brushed Aluminum (AL)

Standards: ETL/cETL, Damp location listed, JA8 2016 Title 24 Compliant





18["] Min

120" Max

ORDER NUMBER

Model	Size	Watt	LED Lumens	Delivered Lumens	Finish
PD-33718	18"	22W	1495	940	
PD-33732	32"	88W	6340	4435	WT White BK Black
PD-33743	43"	125W	11115	7300	AL Brush Aluminum
PD-33753	53"	169W	12028	8458	

Example: PD-33732-BK

dweLED.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122

52½"

PD-33753

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

dweLED retains the right to modify the design of our products at any time as part of the company's continuous improvement program. FEB 2019